

CLAIMS

I claim:

1. A digital video disc holding assembly for selectively positioning on a back side of a vehicle seat, said assembly including:
 - a panel having a first side, a second side, a bottom edge, a top edge, a first lateral edge and a second lateral edge;
 - a plurality of pockets being attached to said first side of said panel, each of said pockets having an open upper end for selectively accessing an interior of said pockets, each of said pockets having a width equal to at least 5.50 inches, a depth equal to at least 0.50 inches and a height equal to at least 3.0 inches, said plurality of pockets being arranged in a plurality of rows extending between said first and second lateral edges;
 - a plurality of flaps, each of said flaps having an attached edge being attached to said first side of said panel, each of said flaps being positioned adjacent to one of said plurality of pockets, each of flaps having a free end being selectively positionable in a closed position extending over an adjacent open upper end or in closed position extending away from said panel, a distance between each of said attached edges and a bottom of an adjacent one of said pockets being at least 7.50 inches; and
 - at least one coupler being attached to said panel for selectively attaching said panel to the vehicle chair such that said second side is abutting the chair.
2. The assembly of claim 1, wherein said panel is selectively foldable along a central area extending between said first and second lateral edges such that said top edge may be selectively positioned adjacent to and aligned with said bottom edge.

3. The assembly of claim 2, wherein said plurality of pockets is arranged in a plurality of rows extending between said first and second lateral edges.

4. The assembly of claim 3, wherein said panel has an equal number of rows between said top edge and said central area as between said central area and said bottom edge.

5. The assembly of claim 4, wherein each of said rows has three pockets therein.

6. The assembly of claim 4, wherein said panel has four rows of said pockets positioned thereon.

7. The assembly of claim 1, further including a plurality of fastening members, each of said fastening members being attached to one of said flaps for removably attaching said free ends in said closed position.

8. The assembly of claim 7, wherein each of said fastening members comprising a hook and loop fastening means.

9. The assembly of claim 7, wherein said at least one coupler includes a pair of couplers.

10. The assembly of claim 9, wherein each of said couplers includes a first pair of straps positioned adjacent to said top edge and a second pair of straps positioned adjacent to said bottom edge, securing means being attached to each of said first and second pairs of straps for releasably attaching associated ones of said straps together such that a pair

of loops is formed, each of said loops being selectively positioned around the vehicle chair.

11. The assembly of claim 1, wherein said at least one coupler includes a pair of couplers.

12. The assembly of claim 11, wherein each of said couplers includes a first pair of straps positioned adjacent to said top edge and a second pair of straps positioned adjacent to said bottom edge, securing means being attached to each of said first and second pairs of straps for releasably attaching associated ones of said straps together such that a pair of loops is formed, each of said loops being selectively positioned around the vehicle chair.

13. The assembly of claim 2, further including a pair of handles, each of said handles being attached to one of said bottom and top edges.

14. The assembly of claim 13, wherein each of said handles extends away from said panel and being angled away from said second side of said panel.

16. The assembly of claim 2, further including a plurality of fastening members, each of said fastening members being attached to one of said flaps for removably attaching said free ends in said closed position.

17. The assembly of claim 16, further including a pair of handles, each of said handles being attached to one of said bottom and top edges.

18. The assembly of claim 17, wherein each of said handles extends away from said panel and being angled away from said second side of said panel.

19. A digital video disc holding assembly for selectively positioning on a back side of a vehicle seat, said assembly including:

- a panel having a first side, a second side, a bottom edge, a top edge, a first lateral edge and a second lateral edge, said panel being selectively foldable along a central area extending between said first and second lateral edges such that said top edge may be selectively positioned adjacent to and aligned with said bottom edge;

- a plurality of pockets being attached to said first side of said panel, each of said pockets having an open upper end for selectively accessing an interior of said pockets, each of said pockets having a width equal to at least 5.50 inches, a depth equal to at least 0.50 inches and a height equal to at least 3.0 inches, said plurality of pockets being arranged in a plurality of rows extending between said first and second lateral edges, said panel having an equal number of rows between said top edge and said central area as between said central area and said bottom edge, each of said rows having three pockets therein, said panel having four rows positioned thereon;

- a plurality of flaps, each of said flaps having an attached edge being attached to said first side of said panel, each of said flaps being positioned adjacent to one of said plurality of pockets, each of flaps having a free end being selectively positionable in a closed position extending over an adjacent open upper end or in closed position extending away from said panel, a

distance between each of said attached edges and a bottom of an adjacent one of said pockets being at least 7.50 inches;

a plurality of fastening members, each of said fastening members being attached to one of said flaps for removably attaching said free ends in said closed position, each of said fastening members comprising a hook and loop fastening means;

a plurality of couplers being attached to said panel for selectively attaching said panel to the vehicle chair such that said second side is abutting the chair, said plurality of couplers including a pair of couplers, each of said couplers including a first pair of straps positioned adjacent to said top edge and a second pair of straps positioned adjacent to said bottom edge, securing means being attached to each of said first and second pairs of straps for releasably attaching associated ones of said straps together such that a pair of loops is formed, each of said loops being selectively positioned around the vehicle chair; and

a pair of handles, each of said handles being attached to one of said bottom and top edges, each of said handles extending away from said panel and being angled away from said second side of said panel.